



Maintenance Solutions

Pro Staff

Ultra High Speed
Low Maintenance
Finish

For Use On:

- | | |
|----------------|-------------|
| Vinyl Tile | Rubber Tile |
| Vinyl Asbestos | Terrazzo |
| Asphalt Tile | Sealed Wood |
| Linoleum | Quarry Tile |



DESCRIPTION

An ultra hi-speed floor finish designed specifically for the professional that needs unsurpassed "wet look" gloss with excellent durability and dirt release, yet is simple to apply and maintain. Requires no sealer when used on resilient tile floors, however a sealer should be used when applying to non-resilient type floors. Maintainers or restorers are not required when burnishing. Response is unsurpassed with any type of UHS equipment-propane, battery, or cord electric.

DIRECTIONS

PREPARATION: If stripping is necessary, use a high quality stripper and follow directions accordingly. If floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow to dry completely.

FINISHING: Apply 2 or 3 liberal coats of finish using a clean mop. Allow 30-45 minutes drying time between coats. Apply additional coat to obtain desired gloss.

BURNISHING: Dust mop or sweep thoroughly. Clean floor with a neutral floor cleaner diluted according to directions. Burnish using the appropriate pads.

RECOATING: Dust mop or sweep thoroughly. Deep scrub using a neutral floor cleaner diluted according to directions. Apply 1 or 2 liberal coats of finish using a clean mop.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations.

PRODUCT SPECIFICATIONS

Type:	Modified acrylic	Removability:	With instant type strippers
Non-volatile solids:	22.0±0.5%	Detergent Resistance:	Excellent
Color:	Milky white	Waterspot Resistance:	Excellent
Odor:	Mild	Heel Mark Resistance:	Excellent
pH:	8.5 - 9.0	VOC Content:	0.39 lbs./gal.
Dry/Recoat Time:	45 minutes min.	Storage/Stability:	2 years
Slip Resistance:	.5 min by ASTM D2047	Freeze/Thaw Stability:	Keep from freezing
Gloss:	90+ specular	Weight per Gallon:	8.54 lbs./gal.
Leveling:	Excellent	Coverage:	2000-2500 ft ² per gal.
Buffability:	Dry burnishable		

Floor Finishes & Waxes

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Manufacturer's Name: Misco Products Corporation	Product Name: Pro Staff	Supplier's Name:
Manufacturer's Address: 1048 Stinson Drive Reading, PA 19605	Generic Name: Ultra High Speed Floor Finish	Supplier's Address:
Manufacturer's Phone #: (610) 926-4106	Chemical Family: Acrylic Wax Blend	Supplier's Phone #:
	Formula: Proprietary	

SECTION 2-INGREDIENT INFORMATION

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Acrylic Copolymer Dispersion	65405-61-0	45 to 50			
Polyethylene Wax Emulsion	68441-17-8	10 to 15			
Tributoxy Ethyl Phosphate	78-51-3	0 to 5			
Diethylene Glycol Monomethyl Ether	111-77-3	0 to 5			

SECTION 3-PHYSICAL DATA

Boiling Point (°F): 212 F. **Specific Gravity:** 1.025
Vapor Pressure: 20mm Hg @ 68 F. **Vapor Density (Air=1):** >1
% Volatile: 75+ **pH:** 8.5-9.0
Solubility in Water: Complete **Evaporation Rate (Water=1):** <1
Physical Description: Thin milky liquid with characteristic odor.

SECTION 4-FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/A
Upper Explosion Limit: N/A **Lower Explosion Limit:** N/A
Extinguishing Media: N/A
Special Firefighting Procedures: Non Flammable
Unusual Fire and Explosion Hazards: N/A

SECTION 5-REACTIVITY DATA

Stability: Stable **Hazardous Polymerization:** None
Hazards Decomposition Products: Will not occur. **Incompatibility (Materials to Avoid):** None

SECTION 6-STORAGE AND HANDLING INFORMATION

Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Avoid breathing of vapors. Use in well-ventilated area.

SECTION 7-HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:
Skin: Prolonged or repeated contact may cause dermatitis.
Eyes: Eye irritant. May cause redness or swelling.
Inhalation: Vapors may cause headache, dizziness, nausea.
Ingestion: May be irritating to the mouth, throat, and gastrointestinal system.
 Vomiting and diarrhea expected with large doses.

First Aid Procedures:

Skin: Flush with water. Seek medical attention if irritation persists.
Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.
Inhalation: Remove victim to fresh air and monitor.
Ingestion: Dilute with 2 glasses of water. Seek medical attention if symptoms persist.

SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use in well-ventilated areas.
Ventilation Requirements: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit.
Protective Gloves: Chemical resistant rubber or neoprene.
Eye Protection: Safety glasses or chemical splash goggles
Other Protective Equipment: Protective footwear (rubber boots) should be worn when using product on floors.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.
Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not dispose of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash.

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories:
 No - Fire Hazard
 No - Sudden Release of Pressure Hazard
 No - Reactivity Hazard
 Yes - Immediate (acute) Health Hazard
 No - Delayed (chronic) Health Hazard

Shipping Information:
 FOR CONTAINERS > 1 Gallon : Liquid Floor Wax
 FOR 1 GALLON CONTAINERS : Liquid Floor Wax
 FOR CONTAINERS < 1 GALLON : Liquid Floor Wax

HMIS Hazardous Materials Identification System

Health	1
Flammability	0
Reactivity	0
Personal Protection	A

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: CHEM-TEL, Inc. @ 800-255-3924 (24 hours, 7 days per week)

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS#	Chemical Name	Percent by Weight
	None	

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

CAS#	Chemical Name	Percent by Weight
	None	

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product